

## Aquatest 1010 Titrator Specifications:

Method:	Coulometric Karl Fischer Titrimetry
Detections:	Constant Current Polarization
Titration Control:	Automatic Electrolysis Current Control
Electrolysis Current:	Maximum: - 342.7 mA
Titration Rate:	Maximum: - 32 µg H <sub>2</sub> O/sec.
Background:	Automatic Correction, up to 70 µg H <sub>2</sub> O/min
Measuring Range:	10 µg to 100 mg H <sub>2</sub> O
Sensitivity:	0.1 µg H <sub>2</sub> O
Precision:	± 3 µg for 10 µg to 1 mg H <sub>2</sub> O C.V. = 0.3% or less for 5000 µg H <sub>2</sub> O or more
Display:	4 x 20 alpha numeric LCD display
End Display:	Message Display, Electronic beep and LED indicator.
Calculation:	Concentration (µg, %, ppm,)
Printer:	Optional Thermal Dot Matrix Printer Paper Width 57.5 to 82.5 mm
Self-Diagnostics:	Electrolysis Current, Detection Control.
Memory Back-up:	1 year
Other Functions:	RS-232 Printer/Computer Interface GLP formatted Data Output
Ambient Temperature:	5° to 40° Celsius
Ambient Humidity:	Less than 85%. No Condensation of Ambient Moisture
Power Requirement:	AC 100V- 240V, 50/60Hz, 1.5A
Dimensions:	Case: 125mm (W) x 310mm (D) x 145mm (H) 5" (W) x 12.3" (D) x 5.8" (H) Terminal: 106mm (W) x 195mm (D) x 36mm (H) 4.2" (W) x 7.7" (D) x 1.4" (H)
Weight:	Approx. 2.3 kg (5.0 lbs.)

*Creating precision instruments since 1939*

### ***Photovolt Instruments Inc.***

6323 Cambridge Street  
Minneapolis, MN 55416  
Phone: 952.848.2000  
1.800.222.5711  
Fax: 952.926.5498  
Internet: [www.photovolt.com](http://www.photovolt.com)  
E-mail: [sales@photovolt.com](mailto:sales@photovolt.com)

